

Phone: 952-442-7520 Fax: 952-442-7521

Email: infoMN@safebuilt.com

INTERIOR DRAIN TILE

➤ Th	nis handout is	intended only	/ as a guide.	It shall not be	considered a co	mplete set of	i requirements
------	----------------	---------------	---------------	-----------------	-----------------	---------------	----------------

- > Materials and installation must comply with the current Minnesota State Building Code and the manufacturers' installation specifications for each product.
- > Permits are required to add interior drain tile to existing homes.

BUILDING Permit Submittal shall include:

Building Permit Application , comp	bleted in its entirety, <u>including signature and valuation</u> .				
One set of plans (drawn to scale) showing the proposed design, and including:					
□ Location of drain tile	□ Location of sump basket				
□ Drainage system type	□ Location of sump discharge				

PERMIT CARD AND APPROVED PLANS (throughout the project) shall be:

POSTED prior to start of work - VISIBLE from street or driveway - ACCESSIBLE to the inspector

INSPECTION REQUIREMENTS:

Inspections **MUST** be scheduled during office hours **AT LEAST** one business day prior to inspection. If a specific date and time is required, additional notice may be needed. Failure to cancel a scheduled inspection may result in a reinspection fee.

- o Office Hours: Monday Friday 8:00 a.m. 4:30 p.m.
- o **Phone:** (952) 442-7520 or (888) 446-1801

<u>Inspections</u> (See your permit card for required inspections for your particular project. Following are descriptions of some of the possible required inspections related to drain tile work.):

- o Someone 18 years or older must be present at the time of the inspection.
- Rough-in: Inspector should be able to see trench, drain tile, gravel or crushed rock, and vapor retarder – PRIOR TO POURING NEW CONCRETE.
- o **Final:** Concrete should be poured and system installation complete, with discharge lines installed.

NOTICE: Construction or work for which a permit is required shall be subject to inspection by the Building Official, and such **construction or work shall remain accessible and exposed for inspection purposes until approved.** It is the responsibility of the permit applicant to be in attendance on site and provide access to the Building Official for all required inspections. If work is concealed and/or work is not complete at time of inspection, an additional inspection is required and a **reinspection fee may apply.**

Note: The State of Minnesota requires all residential building contractors, remodelers, roofers, plumbers, and electricians to obtain a state license, unless they qualify for a specific exemption. Any person claiming an exemption must provide a copy of a Certificate of Exemption from the Department of Labor & Industry to the Municipality before a permit will be issued.

Note: To determine contractor requirements, or to check the licensing status of a contractor, please call the Minnesota Department of Labor & Industry at 651-284-5065 or toll free 1-800-342-5354.

Note: For specific code requirements, contact the Building Inspection Department at 952-442-7520 or 888-446-1801 or e-mail: infoMN@safebuilt.com.

PROJECT INFORMATION:

I ROJECT IN OKTATION.
The following is a guideline to assist in compliance with the requirements of the MN State Building Code.
 □ Drain tile or pipe must be at least ≥ 3" in diameter (MN Plumbing Code 1101.5). □ ¾" minimum washed gravel must cover the pipe by more than 4" on all sides (MN Plumbing Code 1101.5).
Minimum slab thickness is to be 3½" (MN Residential Code 506.1).
☐ The discharge line must be 1½" diameter minimum (MN Plumbing Code 1101.5.2).
☐ Discharge line must have a check valve (MN Rules Chapter 1303.2402 Subpart 4, E).
Sump pump must have ≥ 15 gallons per minute flow rate (MN Plumbing Code 1101.5.2).
Sump basket must be a minimum of 15" in diameter and 18" deep, with a fitted, gasketed, and a
secured cover (MN Plumbing Code 1101.5.2).